


U60 LON[®] FT & TP-1250 USB DIN Modules



U60 expansion modules connect LON devices via USB

Product Description

The U60 network interface expansion modules enable a controller or computer to communicate with LON networks via USB. The compact devices are housed in DIN 43880 2TE compliant enclosures.

The U60 TP-1250 model is an interface to LON/IP TP-1250 and LON TP-1250. The U60 FT model is an interface to LON/IP-FT and LON-FT. Both are compatible with OpenLDV 5 and with hosts implementing the LON/IP stack which provides source code for LON/IP and LON compatible protocol stacks.

The interfaces facilitate communication to everyday devices like pumps, motors, valves, sensors, actuators and lights for process control, building automation, energy management, transportation systems control and telecommunications equipment management.

Tx and Rx LEDs provide an indication of LON packet transmission and reception. An on-board Status or Service LED (see specifications) provides a visual indication of device status; status is also communicated to the host via the USB interface enabling the host controller to monitor Status (TP-1250 model) or provide a network Service indicator (FT model).

Features and Benefits

- USB interfaces for LON FT and TP-1250 networks for any edge server, gateway, controller, or device, including Adesto's SmartServer™ IoT
- Compatible with IzoT[®] Net Server, OpenLNS[®] Server, LNS[®] Server and OpenLDV applications
- Works with IzoT Net and LNS compatible applications such as the IzoT Commissioning Tool and LonMaker Integration Tool
- Compatible with SmartServer IoT
- Compact DIN 43880 2TE form factor
- Powered by 5V USB input
- Source code available as download for a Linux-compatible driver

PRODUCT SPECIFICATIONS

Hardware and electrical specifications

Processor (TP-1250 model):	Adesto Neuron 6050
Processor (FT model):	Adesto FT 6050 Smart Transceiver
LON connector:	1 two-way push clip
Micro-B USB receptacle for connection to the host:	Certified USB 2.0 compatible, compatible with USB 1.1 and high-speed USB systems, peripherals and cables
USB cable:	Includes cable with Micro-B USB to Type A USB
Indicators:	LON Tx/Rx LEDs, Status LED (TP-1250 model), Service LED (FT model)
Connect button:	TP-1250 model
Input voltage:	5VDC USB power
Input current:	110mA maximum USB power
Temperature range:	-40°C to +70°C

Humidity:	10-90% RH @ 50°C
Mounting:	DIN 43880 2TE

Software Platform

Interface (TP-1250 model):	LON/IP TP-1250 and LON TP-1250 (TP/XF-1250) with a Layer 2 or Layer 5 interface
Interface (FT model):	LON/IP-FT and LON-FT (TP/FT-10) with a Layer 2 or Layer 5 interface


Drivers (free downloads from website):

- Linux source code for a U60 network driver
- OpenLDV 5, or newer, driver for Windows (FT model only)

Safety, compliance and warranty

Agency approvals:	MET 60950, TUV EN 60950, CE, C-Tick
EMC:	FCC Part 15 Class A, EN55022 Class A, EN55024, CISPR 24 Class A
Warranty:	1 year limited warranty

DIMENSIONS, MOUNTING AND CONNECTIONS



The U60 modules are designed for DIN-rail mounting; dimensions for both modules are the same

Bottom view (when mounted): USB port, connect button, network connector

Model #	Product Name	Product Description
75060R-30	U60 TP-1250 DIN Network Interface Module	USB interface to LON/IP TP-1250 and LON TP-1250 1.25Mbps twisted pair networks
75060R-40	U60 FT DIN Network Interface Module	USB interface to LonTalk/IP-FT and LON-FT free topology twisted pair networks